



- Existing**
- Boundary
 - Existing trees
 - Existing native hedge retained and under sown with wildflower seed
 - Existing trees and/or vegetation to be removed
 - Existing relocated memorial bench
 - Existing grass retained and overseeded where necessary
- Proposed**
- Semi mature 25-30cm girth tree with staking or underground guying as appropriate
 - Semi mature 20-25cm girth tree with staking or underground guying as appropriate
 - Proposed specimen tree 16-18cm girth or multistem tree 3-3.5m tall
 - Proposed species-rich native hedge 1.5m tall at average 7 per sqm.
 - Proposed ornamental shrub/perennial with feature specimens. 3-5l pots size at average 4 per sqm.
 - Proposed native structure planting. 80-100cm whips in native species with average 5 per sqm.
 - Proposed amenity turf
 - Proposed wildflower seeding
 - Earth mounding
 - Steel and timber seat 1500mm long. Broxap Ravenstone Seat from Broxap or similar approved
 - Timber seat 2000mm long. Woodscape Backless curved or similar approved
 - Stainless steel bollard Broxap Mitred Top Sheffield with reflective strip or similar approved
 - Stainless steel door barrier. Broxap 88x4 6620 Door Barrier or similar approved
 - Powder coated cycle shelter. Broxap Apollo Cycle Shelter or similar approved. Size dependant on cycle number
 - Pedestrian Bitmac footpath with concrete pin kerb
 - Natural stone slab paving. 450mm x various. Marshalls Grabe Mid/light grey, blast finished or similar approved
 - Exposed aggregate paving. 450 x various. Marshalls Conservation textured Silver grey or similar approved
 - Exposed aggregate block paving. 360 x various. Marshalls Conservation textured charcoal or similar approved
 - Composite Timber Deck. Millboard Lasta Grip in Coppered Oak or similar approved. Suspended on ground screws - see ZLA_1302-L-303 for further details.
 - DDA Compliant steps, to include handrails, nosing demarcation and tactile paving
 - Bespoke timber seating and canopy. See ZLA_1302-L-303 for further details
 - Tactile/hazard paving 450 x 450mm marshalls textured natural or similar approved
 - Drop Kerb. To Engineers specification and detail
 - Suggested location of retaining wall - to Engineers approval and detail

